



# APPROVAL OF MANUFACTURER CERTIFICATE

Certificate No:  
**AMMM00000D1**  
Revision No:  
**4**

This is to certify:

That

**Deutsche Edelstahlwerke Witten/Krefeld GmbH & Co. KG**  
**Auestraße 4, 58452 Witten,**  
**Germany**

is an approved manufacturer of  
**Steelmaking and Rolled Steel Products**

in accordance with

**DNV rules for classification – Ships**  
**DNV rules for classification – Naval vessels**  
**DNV class programme – DNV-CP-0242 Semi-finished steel products**  
**DNV class programme – DNV-CP-0243 Rolled steel products – non stainless steel**  
**DNV class programme – DNV-CP-0244 Rolled steel products - stainless steel**

and the following particulars:

<b>Product</b>	<b>Semi-finished products</b>
<b>Steel type</b>	<b>Rolled bars intended to be machined into components</b> <b>Carbon and carbon-manganese,</b> <b>Alloy,</b> <b>Austenitic stainless</b> <b>Austenitic-ferritic (Duplex) stainless</b> <b>Martensitic stainless,</b> <b>Ferritic stainless</b> <b>Special materials for naval ships</b>
<b>Manufacturing method</b>	<b>Electric arc furnace,</b> <b>continuous / ingot casting</b>
<b>Deoxidation</b>	<b>killed</b>
<b>Heat treatment condition</b>	<b>See particulars of the approval</b>
<b>Max. thickness/diam.</b>	<b>See particulars of the approval</b>
<b>Additional approval conditions</b>	<b>See particulars of the approval</b>

Manufacturer(s) approved by this certificate is/are accepted to deliver according to DNV GL, DNV and GL rules.  
Materials to be applied to DNV classed object shall fulfill the material requirements in the applicable DNV class rules.

Issued at **Hamburg** on **2025-03-06**

This Certificate is valid until **2026-06-19**.

DNV local unit: **Essen**

Approval Engineer: **Christian Wildhagen**



for **DNV**

This document has been digitally signed and will  
therefore not have handwritten signature

Stefan Röhr

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: AM 311

Revision: 2022-12

www.dnv.com

Page 1 of 3

## Particulars of the approval

### Semi-finished products

Steel type	Product	Steel making <sup>1)</sup>	Max weight [kg]	Max. thickness / diameter [mm]	Heat treatment condition <sup>2)</sup>
C and C-Mn, Alloy, Ferritic stainless, Austenitic stainless, Martensitic stainless, 22Cr duplex stainless, 25Cr duplex stainless	Bloom, Billet, Slab	EAF, CC	-	340	AC
	Ingot	EAF, IC	40 000	1 850	AC
	Bar	EAF, CC or IC	-	250	AR

### Rolled bars <sup>4)5)</sup> intended to be machined into components (as a substitute for forged bars)

Steel type	Grade <sup>3)</sup>	Max. Diameter [mm]	max. Length [mm]	Max. Weight [kg/m]	Heat treatment condition <sup>2)</sup>
C and C-Mn	NV F400UW, NV F440UW, NV F480UW, NV F520UW, NV F560UW, NV F600UW	250	27 000	1 500	N, NT, QT
Alloy	NV F550AW, NV F600AW, NV F650AW	250	27 000	1 500	QT
C and C-Mn	NV F400U, NV F440U, NV F480U, NV F520U, NV F560U, NV F600U, NV F640U, NV F680U, NV F720U, NV F760U	250	27 000	1 500	N, NT, QT
Alloy	NV F600A, NV F700A, NV F800A, NV F900A, NV F1000A, NV F1100A	250	27 000	1 500	QT
Austenitic	NV 304L, NV 316L, NV 316LN, NV 317L, NV 317LN, NV 321, NV 347	250	27 000	1 500	SHT
Duplex	UNS S31803, UNS S32750	250	27 000	1 500	SHT
C and C-Mn, Alloy	NV-M550, NV-M700	150	27 000	1 500	QT
	NV-M550S, NV-M700S	200			
	15NiCrMo10-6 acc. WL 1.6780-2 16NiCrMo12-6 acc. WL 1.6782-2	200			
	HY-80 acc. MIL-S-21952D HY-100 acc. MIL-S-21952D	200			
Non-magnetizable	1.3964.9 acc. WL 19364-2	160	27 000	1 500	SHT
	1.3964 acc. SEW 390	250	27 000	1 500	SHT

**Rolled bars <sup>4)5)</sup> intended to be machined into components (as a substitute for forged bars)**

Steel type	Grade <sup>3)</sup>	Max. Diameter [mm]	max. Length [mm]	Max. Weight [kg/m]	Heat treatment condition <sup>2)</sup>
C and C-Mn	S235JR, S235J0, S235J2, S275JR, S275J0, S275J2, S355JR, S355J0, S355J2, S355K2 acc. EN 10025-2	250	27 000	1 500	N, AR
C and C-Mn	S275N, S355N, S275NL, S355NL acc. EN 10025-3	250	27 000	1 500	N
C and C-Mn	acc. EN 10083-2	250	27 000	1 500	N, NT, QT
	acc. ISO 683-3				
Alloy	acc. EN 10083-3	250	27 000	1 500	QT
	acc. ISO 683-3				
Austenitic stainless	acc. EN 10088-3	250	27 000	1 500	SHT
	acc. EN 10272				
Duplex	acc. EN 10088-3	250	27 000	1 500	SHT
	acc. EN 10272				
Ferritic	acc. EN 10088-3	250	27 000	1 500	A
	acc. EN 10272				
Martensitic	acc. EN 10088-3	250	27 000	1 500	QT
	acc. EN 10272				
	1.4542 acc. EN 10088-3	250	2 500	1 500	PH
	Type 630 (17-4PH) acc. ASTM A564				

**Remarks:**

- 1) EAF: Electric arc furnace  
CC: Continuous casting  
IC: Ingot casting
- 2) AC: As cast  
AR: As rolled  
QT: Quenched and tempered  
N: Normalized  
NT: Normalized and tempered  
SHT: Solution Heat Treated (Solution Annealing)  
PH: Precipitation hardened  
A: Annealed
- 3) Incl. equivalent grades in acc. to other standards (e.g. ISO 683-1, ISO 683-2, ISO 683-3)
- 4) Minimum rolling reduction ratio 6:1
- 5) Sampling, inspection and testing requirements shall be according to Rules for ships Pt.2 Ch.2 Sec.6